




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>A61N 1/37</b>	<b>A1</b>	(11) International Publication Number: <b>WO 98/42407</b> (43) International Publication Date: 1 October 1998 (01.10.98)
<p>(21) International Application Number: PCT/US98/06085</p> <p>(22) International Filing Date: 27 March 1998 (27.03.98)</p> <p>(30) Priority Data: 60/042,367 27 March 1997 (27.03.97) US</p> <p>(71) Applicant (for all designated States except US): MEDTRONIC, INC. [US/US]; 7000 Central Avenue Northeast, Minneapolis, MN 55432 (US).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): WEBB, James, D. [US/US]; 8138 Ranier Lane, Maple Grove, MN 55311 (US). NELSON, Chester, G. [US/US]; 6755 Cottonwood Lane, Maple Grove, MN 55369 (US). THEIS, James, G. [US/US]; 11015 Louisana Lane North, Champlin, MN 55316 (US). STAUFFER, Ronald, A. [US/US]; 10784 Kumquat Street Northwest, Coon Rapids, MN 55448 (US).</p> <p>(74) Agents: ATLASS, Michael, B. et al.; Medtronic, Inc., 7000 Central Avenue Northeast, MS301, Minneapolis, MN 55432 (US).</p>	<p>(81) Designated States: CA, JP, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p><b>Published</b> With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</p>	

(54) Title: IMPLANTABLE MEDICAL DEVICE REMOTE EXPERT COMMUNICATIONS SYSTEM FOR COORDINATED IMPLANT AND FOLLOW-UP

## (57) Abstract

A medical device implant, monitoring and adjustment are enhanced by the telepresence of a remote expert (31) having a screen display (30) that mirrors the display at the patient location. Pointers (51), whether they can activate subprograms at the patient location or not, are moved identically at both locations at the same time. Also, the ECG and any features thereof are updated in real time, while other communication operations occur.

**Remote "Experts"**

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**IMPLANTABLE MEDICAL DEVICE REMOTE EXPERT COMMUNICATIONS SYSTEM  
FOR COORDINATED IMPLANT AND FOLLOW-UP**

This invention relates to communication and coordination facilities which enable a remote expert to easily facilitate understanding of communication to a local actor in real time. Particularly, this invention relates to application of such systems to active surgery situations and clinical environments in which the visual display screens of the remote and distant locations must be tightly coordinated, and is especially applicable to such situations where a pointer and a time varying physiological signal may be displayed on the same screens at the same time.

**Background:**

During surgery or for follow-up to determine the present functionality or to change functionality for implanted medical devices, it can be important for an expert at a remote site to know how the implant is responding and what the local actor dealing with the implant and/or the patient is doing in real time. There is very little acceptance for confusion in such circumstances and having a real time system display available to both the remote actor and the local actor will go a long way to eliminating the potential for confusion.

Similar communications and remote functioning have been attempted previously. It is believed that none of the prior systems are particularly well suited to the surgical or clinical environments, and particularly not to those where implanted medical devices are being used. By enabling remote pointing and physiologic display coordination, rapid and exact communications about the condition of the device and/or the patient and any peculiarities in the display can be noted and controlled for across large distances. Thus a single expert could be "virtually" at many distant locations in a single day using such a system without leaving the situs of his computer. A list of references where similar inventions in the same or other fields were contemplated follows, and these are incorporated herein by this reference thereto.

Epard et al, US Pat. No 5,241,625,  
Inga et al., US Pat. No 5,384,643,  
Thompson US Pat. No 4,377,852,  
5 Ziv-El US Pat. No 5,263,869,  
Thessin et al. US Pat. No 5,452,299,  
Harlan US Pat. No 5,168,269,  
Torok, et al. US Pat. No 4,317,956,  
Stein et al. US Pat. No 4,098,267, and  
10 Bijnagte US Pat. No 5,235,680.

There have been remote device operations used before, wherein a remote expert could control what was occurring on a local technicians station, including for example, the model 89441a Vector Signal Analyzer(TM) from Hewlett Packard, but  
15 no prior devices of which the inventors are aware include the features of this disclosure which are particularly suited to remote expert supervision of a local implantable medical device operation. The instant disclosure relates particularly to allowing for repeatable remote near real time ECG, EGM, and marker channel information at the same time display and allowing for dual site manipulation of a  
20 pointer on the display at both locations without having conflict. [In this document we will use various terms such as ECG, EGM, EKG and Marker Channel information to represent that such types of information as the intracardiac electrogram or surface ECG's, with or without additional marker channel information are all signals that could be found in the display window from whatever  
25 physiologic signal that the local attendant and remote expert may desire to look at simultaneously. Accordingly, any such use of these terms should be assumed to apply to the use of any of these terms for any similar physiologic signals, with or without device information superimposed thereon, such as Marker Channel information.]

The primary use of the invention is believed to be pacemaker/defibrillator follow-up and implant where an expert is remote from the patient's local situs where such operations are occurring. What is believed to be needed is a communications system for communicating in real time or near real time the position of a pointer that is manipulable at more than one location on simultaneous displays at two locations so that the pointer will appear at the same location in the remote display as the local display regardless of any conflicting instructions given by users at the remote and local locations. Provision is made to allow for simultaneous activation of two pointers, one controlled by the expert and one by the attending technician/physician. Each has a unique icon in our preferred system embodiment.

This system should have simultaneous displays for communicating and where necessary, enhancing the ECG signal available for remote display such that it appears to move like a normal ECG at the remote location with minimal difficulty and movement occurs in near real time. Of particular concern in using typical remote viewing systems is that screen displays occasionally have lossy displays, so a short term change in a physiologic signal may be missed at the remote location. The sweep-bar or smooth movement of the signal should ideally be maintained. The availability of such a system would help a great deal in surgery and particularly cardiac surgery. It could also find application to the cardiac pacemaker clinic follow up. With a coordinated cursor or pointer only one of the remote and local actors can adjust its position at a given moment, and there can be no confusion as to what location in the display they are both communicating about through some other telephonic aural or video link which should be operative simultaneously to best employ the inventive features described herein.

What such a system would enable is the review by an expert on either the patient (as in a doctor, for example) without this expert needing to be present in real space. It alternatively and simultaneously could be used for the consultation of a local physician or surgeon with a systems expert that may have intimate knowledge

about the components of the devices that are generating the EKG signal and performing other functions in the surgical or clinical locality.

#### **Brief description of the drawings**

Fig. 1 is an overview of the " local" environment having a physician, patient, and programmer device present.

Fig. 2 is a simplified representation of any data communications system.

Fig. 3 is an illustration of a distant expert and his computing device.

Fig. 4 uses a communications layer block diagram illustrating " MedConnect " layers and related communications layers in accord with a preferred embodiment of the invention.

Fig. 5 is an alternative view of the communications interface illustrated in Fig. 4, expanding on the details of the communications layer depicted in Fig. 4..

Fig. 6 is a stack diagram of communications and protocol layers providing an alternative representation of Fig. 5.

Fig. 7 is an illustration of a two color (8 bytes to 1 byte) video data compression scheme used by a preferred embodiment.

Fig. 8 is an alternative graphic representative illustration of the relationships of the communications linking arrangements displayed in Fig. 6.

Fig. 9a illustrates an ECG display window which would be a single element on a display screen in accord with a preferred embodiment.

Fig. 9b. illustrates three data packets that may be organized as shown for preferred embodiments of the invention.

5 Figs. 10a and 10b are block diagrams illustrating how program controls provide coordination between remote and local ECG data.

Figs. 11-14 are illustrations of screen displays in accord with preferred forms of this inventions.

10 Fig. 15 is a heuristic diagram of system components and their interaction in accord with a preferred embodiment.

15 Fig. 16 is a heuristic diagram having a blown up portion illustrating the arrangement of video RAM data memory organization relative to an area of video display.

### **Summary of the invention**

20 Various aspects related to remote communications are herein described with particularly here and claimed, those improvements provide a new system image the features of a moving remote ECG or other physiologic signal display and real time remote pointer coordination.

25 In general a personal computer with a microprocessor and memory that contain appropriate software to configure them to operate as detailed herein is connected to a programmer which has similar and interrelated components, via any one of a number of methods including modem connections over telephone lines, DSVD modems, wireless, or internet, or any other similar form of communications  
30 link that may be in use and easily available. In other words, the system would

employ a set of at least two devices having a display at a remote and at an operating location and communications pathways between, that communicate a coordinated display of information on the remote location display and in the operating location display such that communications are enhanced between the users at the two locations by use of the two coordinated display means at the remote and local operating (i.e. programmer) locations. The local display may also display local information to the local user that is uncoordinated with or completely separate from information displayed at the distant site display if desired. For examples, a battery power available display may appear on a local portable device display, that is unnecessary for the distant location to be aware of; or an expert system window could be available to the local display of the remote expert actor which is unavailable to the display at the location of the operating room surgeon.

At one end is the programmer device for use in medical communications systems for communicating in near real time information from between at least two remote sites, one remote site at a patient location having the programmer device which has a programmer generated display, and an other of said at least two remote sites at an expert location having a computing device with a computing device generated display, each location having available substantially similar screen displays, such that information related to an implantable medical device and a patient at said patient location remote site can be reviewed simultaneously on said substantially similar displays at said at least two remote sites facilitated by data communications transferred across a communication line between said at least two remote sites, said programmer device being configurable to perform various operations by executing programs through a microprocessor and memory system although many of the programs could be converted to hardware having limited functionality. This programmer then would have a physiologic signal device connection, connected to said programmer device for receiving electrical output representing a patient's physiologic signal waveform ,and for producing a signal suitable for use by a programmer screen display operating program for generating a



display from said electrical output at at least one display area including at least a physiologic waveform signal display area and producing instantaneous changes in said at least one display area, at least one of said changes representative of changes in said waveform. The programmer display operating program, would use a  
5 number of elements including at least

a first video display data buffer for holding a video data representation of information displayed in one of said at least one display areas of said programmer generated display,

10 a second video display buffer for holding data representing instantaneous changes in at least one of said areas,

a display generating program for using a data image of said video data representation in said first video display buffer for producing said programmer generated display, and it would also have

15 an index generating program for reviewing data in said first video display buffer and creating a first index buffer corresponding to said at least one of said display areas, said index generating program indicating in said first index buffer by storing data therein representing which of all locations in said at least one area have changed from a previous review, and for capturing a data representation of said changed locations in a capture buffer and, a sending program for packaging data  
20 comprising contents of said first index buffer and said capture buffer in appropriately encoded format, and for sending said appropriately formatted index buffer data across the communication line so as to get the information to the other remote site(s).

25 Preferably, the display generating program also has a two color display generating program for interpreting said physiologic signal waveform as two color display data, and wherein said index generating program has a data compression program for receiving said physiologic waveform index data and coding it such that for each byte, one bit is set to indicate whether a change has occurred in that byte

and such that for the entire physiologic waveform index buffer, a compressed physiologic waveform index is prepared.

5 The programmer operating program preferably also has a pointer/cursor coordination program having a buffer for holding at least location information for each pointer/cursor to be coordinated, and having a monitoring means for updating any programmer generated display change in pointer/cursor activation and location, said monitoring means updating each said pointer/cursor buffer with any change in location information from a last review, said location information being changeable responsive to pointer/cursor user controls based on a local user changing location status of any pointer/cursor under local control, and wherein said pointer/cursor coordinating program further comprises a buffer for containing information regarding at least location status of each remote pointer that is to be displayed on said patient location display. The programmer operating program having these 15 pointer/cursor features operates with the patient location screen display operating program, which to work with these pointer/cursor features has a program for receiving new information for each said remote pointer/cursor buffer and operating on such data to produce a display of said remote pointer/cursor in accord with the data in said remote pointer/cursor buffer such that any changes in the location data of a remote pointer/cursor buffer results in a change in location on the display of 20 that remote pointer/cursor on the patient location display screen.

25 Preferrably, the pointer cursor operating program also has an activation buffer for maintaining activation status for each pointer/cursor capable of activation. But if activation is not available from a remote pointer/cursor, such a buffer would not be needed for the activation status of that particular icon, although it could be useful information and used at the programmer site to inform the programmer user that the expert has indicated that the expert thinks this particular pointer/cursor should activate a particular function, even if it is not activatable by the expert

communicating from the remote site. In some embodiments the expert will be able to remotely activate features on the programmer though such a feature.

5 Of course, to activate the features of pointer/cursors we prefer to include in the programmer device a pointer data capture program for capturing and then for sending the data in said pointer/cursor buffer to said communication line.

10 Additionally, we prefer to include a program for monitoring which of all said pointer/cursors is active such that said active cursor/pointer may initiate a command, and for maintaining a data buffer containing such monitored information.

15 Preferably, the computing device operating program for coordinating a physiologic waveform display with a programmer generated display will have a communication means to receive data sent by said programmer device and to produce a physiologic waveform display therefrom.

20 On the other side of the system(s) we prefer a computing device operating program for displaying an image substantially the same as the display on the programmer generated display having communications means to receive data sent by the programmer and generating a substantially similar display therefrom.

25 This of course preferably comprises a system for displaying substantially the same image on at least two remote locations having a programmer device and a computing device as set forth above.

The invention, then, can be described as a method for communicating between at least two remote locations so as to enable coordinated display of a physiologic waveform and pointer/cursor information which preferably has these steps:

capturing pointer/cursor information regarding a location on a display screen  
for each said pointer/cursor,

redacting image data from a video display buffer based on said  
pointer/cursor information so that the remaining video buffer data represents a  
display sans said pointer/cursors

reviewing the redacted video image buffer so as to locate any changes since  
a last review,

creating an index of information describing which locations in said video  
buffer contain changed data since said last review,

capturing representations of the images at the changed locations and storing  
this as data in a buffer,

compressing the index and the capture buffer data,

sending the compressed index and capture buffer data from one of said at  
least two locations.

Preferably, said pointer/cursor data is sent in said sending step.

It can also be described as a method of communicating between at least two remote  
locations so as to enable coordinated display of a physiologic waveform and  
pointer/cursor information preferably having these steps:

receiving compressed index and capture data across a communication line  
from one of said at least two locations at a first of said at least two locations,

decompressing said index and capture buffer data,

swapping in information from said capture buffer data at locations in a video  
display buffer representing corresponding locations to those indicated in said index  
data so as to enable a display at said first location to display said changes.

A preferred form of the method includes in the step of receiving data  
representing pointer/cursor location on a display screen from said one location of at  
least two remote sites and a further step of displaying an iconic image of ca

pointer/cursor representing a pointer displayed at said one remote location in a location on the screen in said first locations indicated by the received representative pointer /cursor location data.

#### **Detailed description of preferred embodiments**

It should be noted that several of the terms used within this document are peculiar to particular companies systems. For example, the term 9790 is the name of a programmer used for programming implantable devices produced by Medtronic, Inc and well known in this field. The 'Macintosh' or 'Mac' is the name of the operating system/user interface for Apple Computer company's computers. E C G and E K G are abbreviations discussed in the background section. Minix 8340 is a name for a particular implantable pacemaker produced by Medtronic, Inc.

Numerous terms are also employed which have common computer and communications industries meanings including, PC, meaning a small or "personal" computer, " application", "layer", TCP, RS-232, and other terms have their commonly used and known meanings also.

In its broadest form, the invention operates in a system having at least those parts heuristically illustrated in Figs. 1-3. In fig. 1, a programmer 10 ( a Medtronic 9790) operates as the local device having a display 10a and input mechanisms for use by a clinician 12 who may be examining a patient 11. fig. 2 briefly illustrates that communication channels may include phone lines 20 to provide data transmission as well as voice communication between the device illustrated in fig. 1 and the device of fig. 3, a physician, company representative, or other expert 31 one may be used the communications device 30. In both Fig. 1 and in Fig. 3, are device 15 and 32, respectively, which illustrate that an additional communications device and/or channel is useful for the best operation of inventive system.

Fig. 4 illustrates in diagram form, a version of the same system 40 as was described with respect to Figs. 1-3, as essentially of two parts, a part 41 local to the expert but remote to the clinician, and a part 42 local to the clinician but remote from the expert. In the preferred embodiment, connects between the pacing expert 31 and the remote user 12 via modem 15, 17 or any other type of modem. Here, a cellular phone 16 may connect to the modem instead of using wire connections as just another example of the realm of possible system communications components. Video and/or audio connections 13,14 may additionally be maintained to facilitate the communications between the user and the expert. With this setup, the data on the remote access system 21 at the expert's site can send and receive data, be in communication with the "VTRX" and other programmer software applications running at the remote user site. (VTRX is a particular kind of system like a DOS or Windows or OS/2 operating system from Microsoft or IBM, but it has some features for running applications in programmers not normally found in the other OS's). There does need to be some coordinating program, here called remote access 18 at the user site that is designed to understand the suitably configured data streams sent between the remote access program at the expert site and the data streams and programs that use them at the user site.

It is important to note that there are various levels of communication required in order for the user accessible high level display programs in the remote access device 21 and the related programs in the expert device to be coordinated. In Fig. 5, the system 50 is illustrated having a logical facilitated communications link 51 between each of the operating layers of the displays at each location. For device 41a and device 42a, a software layer management connection 54a and 54b respectively, must be communicating in a cooperative manner. Additionally, a communications control layer 53a and 53b must pass the working information from the connection management layer to the capability layer 52a and 52b, in order for the cooperation to be accomplished.

A more typical figure for explaining the interrelationships between protocol layers is in Fig. 6. Referring now to Fig. 6 it first must be recognized that the entire column for the preferred MedConnect system would exist at both the expert and patient sites. Remote access software at both sites is depicted in block 63. The columns to the left of the "MedConnect" column depict mappings to other existing communications architectures that may alternatively be used or which may communicate with the MedConnect system. Blocks 63a and 63 together equate to the TCP/IP concept of an Application block 62 or the ISO/OSI concepts of Application layer 61 and Presentation layer 61b. Block 63b equates to the TCP/IP concept of the Transport Control Protocol or the ISO/OSI Session Layer 61c and the Transport Layer 61d.

Also, as would be understood by communications workers familiar with such diagrams, the column under "MedConnect" in most embodiments names the layers of hardware and software from the user application to wires and back through which any data must flow. In other words, the application layer passes data through each layer beneath it and from one set of wires at layer 63z, back up into another identical column at the remote location to block 63 in the most preferred or MedConnect to Medconnect embodiment. It is also recognized that not all uses will be of the proprietary MedConnect protocol so the communication to applications in columns 62 and 61 can also occur, although through different layers as shown in those columns. Thus in one preferred form, it can be seen at 61 that a feature in the application layer (block 61a) of the expert system located remotely from the application layer in (the 9790 or similar patient local device) in column 63 must pass data on timing and location that survives numerous translations and communications down into the physical layer across the communications network and back through another physical layer to the remote application at the top of its column. Of particular relevance to the instant invention are blocks 63a, and 63b, which enable the coding and decoding of appropriate information to accomplish the specific inventive coordination tasks. Thus, the presentation layer 61b in the ISO

OSI standard system on the right would contain the decoding and encoding software features necessary to accommodate layer 63a data, and if it did employ session data, it would have to coordinate with the connection layer 63b data in layer 61c and coordinate transport data through layer 61d. The lower layers would just carry the packets and physical signals and should, of course be coordinated in well known manners. However, in the TCP/IP case, the layer 63b could be eliminated as unnecessary. Also, if both systems had all the elements of the MedConnect system column, they would both need the layer 63b. To summarize, there must be a similar protocol stack in each location's system.

Referring now to Fig. 8, this diagram provides an alternative view of one organization for the preferred embodiment communication layers from 86 through 89 at a location within one of our preferred embodiment systems. At the upper level, the application that provides the device functionality at the device site, say for example, enabling pacing system analyzer data to be monitored and used at an implant where leads are connected for testing to a programmer. The application software would control the display on the local screen within the application layer by using the data in the presentation layer 87. In this layer, the display or "prt" cloud 84 contains data used for location and other display functions, (color etc., ) and this data is communicated between the application and the cloud 85(ex by direct links 81 to these particular data values (prt\_ReportMsg, prt\_PointerMsg, and prt\_ScreenDataMsg, among others which are not shown). Each piece or chunk of data for communication can be thought of as being placed into a buffer for formatting appropriately for enabling the communication of that data in the buffer. These buffers are combined into the data blocks or packets shown for example in Fig. 9b. These values are linked to the transport and connection layers as shown. In understanding this diagram of Fig. 8, recognize that the arrows indicate that the cloud doing the pointing is a subset of types that are represented by the general cloud type pointed to.



Application threads 85 exist on both the expert and patient local devices.  
This layer 86 is equivalent to block 63 in Fig. 6.

The applications 85 use the values in these components (e.g.  
prt\_ScreenDataMsg, prt\_PointerMsg, prt\_ReportMsg) to format data  
communications messages between the Expert and Patient devices.  
These components are of a base type prt\_MedConnectMsg. All these message types  
would be contained in the MedConnect Presentation block 63a depicted in Fig. 6

Details below the Transport layer line 88 relate strictly to communicating the  
data between the expert and patient device locations.

The tpt\_Transport base type equates to the block 63b depicted in Fig. 6

The cnt\_Connection base type equates to the blocks below cnt\_Connection  
arrow on Fig. 6.

For specialized different types of communications media there are  
representations given (e.g. cnt\_..... clouds pointing to base type cnt\_Connection  
cloud 84c ) each of which uses generalized abilities of the Base type.

In Fig. 9a, an ECG display window 90 is illustrated, the height of the  
window 93 is constant throughout, and the window itself comprises essentially two  
segments, an active portion 92 and a trailing portion 91. Only a small part of  
window 90 is actively receiving new data at any time in either the remote or local  
device. It is the nature of ECG wave form that only the leading edge is active, the  
rest of the display merely allows the leading edge to travel rightward along the  
screen. Therefore only the active portion needs to be maintained through  
coordination, since the display manufacturing software local to either system can  
simply redraw the element that was in 90 as it moves to the right in any of

numerous well known ways. Thus, while the local device is receiving the actual electrocardiogram from the patient's attached electrodes, it is sending this data to the remote device as it also draws it on the local screen. The amount of data to transfer is very small since only the leading edge needs to be sent. The refresh rate will depend on how wide window 92 is in the preferred embodiment, the baud rate for data transfer(, the size and frequency of the data packets being transferred will affect the baud rate), the speed of the local computing and display device, and the resolution of the image.

However, given sufficient bandwidth, the entire ECG (or other physiologic data signal) display can be transmitted continuously.

Fig. 7 details a data transfer configuration employed by a preferred embodiment, and an explanation of how it works will help to indicate how the data of a screen display is transferred. When used for the ECG display area, we found that the simplest way to transmit a lossless physiological signal was to limit the display to a two color display, such as Black and White. In doing so we could transmit the entire changed area of the screen representative of the physiologic signal that exists at the moment by only transmitting those very small portions that change. Thus the entire line of ECG data could be transmitted in a very short chunk of data. The video RAM (Random Access Memory, a term with its common industry connotations), is divided into indexed area representations each of which indicate whether and what pixel configuration is lit, colored, and so forth. These typically require a full byte for an 8 color pixel and significantly more for any more enhanced pixel representations(like 16-color displays for example). By limiting ourselves to two colors, the pixel is either lit or not lit, thus inherently allowing for a quick compression to a one or zero representing the pixel. Also, by using run length encoding, every byte of identical data becomes a single bit in the transmitted data stream. So referring back to Fig. 7, we have divided the video RAM index into 8 bytes for the area under consideration. If there is a change in any of these

areas, a corresponding bit is set in the data word 81 which will be sent to the remote location indicating which of the areas of the index have changes in the display at the location known to be indicated by that index. Accordingly, the program at the receiving end will expect, for this example, the first and fifth sections need to be updated at its location and will look to the data in the remainder of the data packet or packets being transferred which relate to this index byte 81 for details about changes in those indexed locations. Typically, the X,Y location of each byte will be kept in a look-up table in both locations so the machines at each location can interpret this data as it comes in. The area of the screen which contains the display of the non new portion of the ECG will not be indexed, since it will be computed as the follow through of the leading edge information always received in each information transfer that has a new index byte, in the preferred embodiment.

In general, continuous screen capture is done by repetitively examining video memory, comparing it to the last known state of video memory, and then sending only the data representing the rectangular regions where data has actually changed on the screen. The video memory is read directly and the software screen compare routine finds the changed rectangles. We employ a specific algorithmic process to accomplish the search for changed rectangles set forth in detail in the Appendix, hereby incorporated by reference. The result of using this preferred program (although any one which accomplishes the result would suffice) is illustrated with reference to Fig. 16, wherein a portion of a videodisplay representing the ECG signal display 160 is shown having a one color physiologic waveform line 161 and alternate color surrounding space 162 drawn thereon. (The use of this program or a similar one could also be applied to the rest of the screen but our most pressing concern is for rapid updating of the physiologic waveform data so this is done separately, preferably). The rectangle area 163 is represented by an 8 by 8 area of memory 164 having a block set for each line color and blank for each background color space within the rectangle 163. A row 164 corresponds

to row 80 in Fig. 7, and the compression from the FF representation to a single bit is already shown in this illustration.

5 Using the compression scheme set forth here the changed data is then run-length encoded, packaged with appropriate protocol and sent to the remote device through the various layers as necessary.

10 In the preferred embodiment we also remove any screen pointers from a screen to be sure that they do not appear as part of the signal data before doing the screen capture operation and then with the pointer data there can be replaced, on top of the display of the screen data. Thus the video RAM has an image of the screen without any pointers drawn on it, and the X,Y screen coordinate location allows the operating program to draw the pointers/cursors on the screens where appropriate, painting over the background or any other feature at that X,Y coordinate.

15 It should be noted that other data compression methods, such as run length encoding may be superimposed upon any screen capture data to minimize the amount of data necessary for transfer for large screen areas that are totally one color, or an other, or are a simple stippled pattern.

20 Fig. 9b is a representation of data being communicated between the remote expert and patient sites, having, as shown here a train of data packets 101 - 103 each organized to have its own unique identifying header 104 - 106, respectively. Preferably it is organized as follows. ECG Data 95 is treated as its own data type and sent separately in its own packets. ECG Data 101 can be treated 102 (dotted line) as Other Screen data 103. Other screen data 103 is raw screen pixel data with  
25 no special features identified, and in the preferred embodiment will contain only the changes made from the last time the screen was updated.. Pointer Location data 97 is communicated between expert and patient sites.

In Fig. 15 a more detailed representation of the system 150 than was available in Figs. 1-3 illustrates the system in a more interactive manner. Essentially the system comprises three parts 151, 152, and 153. In part 151 is a patient P with an implanted medical device D capable of transmitting information via RF or H field waves 154o and receiving information via waves 154i. The local computing device PD 158 provides this wireless communications pathway between the implanted device and the local actor 155.

In section 152 the communications channel 159 is merely illustrated by an arrow. The important pieces of information which transit this mechanism 159 are cross over information 2, identity of the controlling system (block 3), whether it is in section 151 or section 153, and what limitations there are on the transfer of who is controlling (block 4). In the cross over information block 2, timing information and size and location information for the leading edge of the E C G display as well as information relating to the current location of the pointer on each local screen.

In section 153 the remote expert 156 operates the computing device 157 connected through section 152 to the computing device 158. As previously indicated expert 156 may also have voice or video over data connections to the section 151 area, here indicated by block 8. A selection indicator block 9 is shown here to indicate that at this moment the remote expert 156 controls the pointer on the screens of both the R D device and on the P D device. Each one of these boxes, except for 6, and 7 which will probably remain constant throughout large portions of each communication, and block 8 which is Voice Over data being carried directly through aural communications between the actors 155 and 156, will probably have some data being transferred in each packet or group of packets of information being transferred between the sites.

To provide a complete understanding of the system we must refer to the screen displays.

Referring now to Fig. 11, a typical PD (Patient site located Device) display screen 110 is illustrated as it would appear on the remote expert's screen. As in most computing devices, there currently exists a background tool bar main menu T.B.m. For this invention we have determined that it is advantageous to use a number of active icons here labeled AI's 1-n. In this display the icon AI1 opens a phone directory when 'clicked' or activated by a cursor, that may allow interaction with the communications programs, or just monitoring of the connection with the expert's device. AI2 and AI3 provide indications of how often the updates occur between the remote and local screen displays, and can be used to change that frequency in preferred embodiments. The next two, AI4 and AI 5 are icons which will be active depending on whether the expert indication pointer is active (AI4 would be highlighted in that case) or whether the expert's enabling pointed would be active, here shown as an icon of a light wand. AI6 indicates the print function, and the designer can include whatever others are desired for a given system set up. The title bar TB, shows that the PD is engaged in a session, or prepared to run a session.

Note there is an arrow Ar, which the expert user has only on his screen, and does not appear on the screen of the patient located programmer. This arrow can be used by the expert to perform auxiliary tasks in background like receiving a data dump (as illustrated in Fig. 14) or for consulting an expert system resident on his computing device or other system on his computer, while at the same time the expert may continue to monitor the PD location.

Here we also have a number of other active buttons on the screen appropriately labeled with their functional title 112-118. For example, the implanted medical device in communication with the local PD here is indicated at site 111, as a Minix 8340 a type of pacemaker. The serial number or other unique identifier could of course be displayed also if desired, perhaps by clicking on the

button labeled Minix 8340. This screen 110 shows the main menu 112. Three sections 113a-c are present which can report data relative to those areas or enable options under button 113c, as well. Using button 116f, for example, the ECG screen area 160 would become active and show the real time ECG form the leads on the patient's body or from the telemetered out information from the implanted device or from a pacing system analyzer if such a device is active and attached to the programmer.

In Fig 12, the expert and the local user can be seen to both have their controlled icons, 119a and 119b, respectively, concentrating on a portion of the ECG display, the expert's pointing to the left of the patient local user's.

Note that the icons for each location are different and unique to that location, even though they may be displayed remotely. This reduces the potential for confusion and enhances accurate and fast communication of knowledge of the situation between the remote users.

On screen 130 in Fig. 13, the menu option displaying pacing parameters 122 is present. It was made active by the expert using his button 135 at the location shown. The expert would then have switched pointers and activated the active button press at the patient local site using indicator 134, indicating a rate of 49 bpm in area 131. Depending on the embodiment, the user may have to activate this rate by moving his own patient local button to this location shown by the expert at 134 or the expert could activate the local programmer if desired. The ability to allow a local expert to actually run the features of the programmer rather than asking the patient local person to do what the remote expert indicates is a matter of preference, and it may be considered better in some situations to keep the remote expert from having the power to modify local programming or it may be considered essential to disallow such distant control.

For the purpose of being complete, note Fig. 14 which has a separate window superposed over the background window of Figs. 11-13. This merely indicates that normal functionality of multithreaded or multiprocessing systems may be maintained in a background mode at either site. The large white space area displays the data dump that informs the expert about the system and the patient he is communicating about. This data dump screen need not be displayed at the patient site, as in the preferred embodiment. To keep this data dump display (or any other local display) completely local, we handle the covered area of the screen in a manner similar to the way we handled the screen area covered by a pointer. That is to maintain the buffer data for the underlying screen separately from the data for the local-only display in relation to a set of X,Y registers that locally maintain the reference to the appropriate screen location. The data in the local-only buffer is then "painted over" the appropriate screen area in accordance with the display routine for the local operating system.

Here the activating pointer or cursor 141 is an arrow, and if it is clicked when located over one of the buttons 144 or 144a, that function will be run by the computer supporting this display 143.

To reiterate and further explain how this pointer coordination is accomplished, we can use a set of registers with the X,Y coordinates of the pointers for both machines at both locations. When any data is received from a remote location, and there is any indication of a pointer move in that data, the registers will be compared with the incoming data for the relevant registers and if a change is found, the program will accommodate it in accord with the appropriateness of the action and by moving the cursor related to that changed data at the local screen. Flow charts in Figs. 10a and b clarifies this matter. In a preferred embodiment we used a standard O S/2 programmer window implementation, the drawing screen driven by the client window procedure and any re-drawing of all or parts of the window is done automatically when the client window procedure receives a



WM\_PAINT message from the system. (OS/2 is an operating system for IBM corporation computers). This WM\_PAINT message used by OS/2 indicates that all or part of the window is invalid and needs to be redrawn. In our implementation, the screen drawing is driven from the individual application and not from a central procedure. This makes it difficult to restore the screen image under the second pointer as it is moving across the screen. A user touch screen may also be implemented and the pointer may be moved by a remote pointer message received from the remote PC if a remote mouse move is received from the remote PC the programmer will change the icon's pointer image to the remote PC representation and then move the pointer to be coordinates defined in the mouse move message. Moving the pointer at the programmer will be ignored and a pointer message will be returned to the remote computer PC with the Coordinates of the screen position being touched at the programmer site.

Generally then, a single pointer can be viewed and used by both the expert location and the programmer. It should be noted that the pointer on the 9790 programmer is touch screen activated. The pointer/cursor is displayed as an icon. It is coordinated, transferred, and displayed separately from the screen image. The icon is removed from the programmer screen, the screen, with the icon removed is what is captured, and the pointer-icon data then is painted over this screen. Messages relating to the data about the pointer/cursor icons must be sent back and forth between the two remote systems when either a touch-screen event occurs on the programmer or the user selects and moves the pointer/cursor icon(s) at the remote expert device. This is done with an input hood which monitors system messages for touch screen or pointer event messages. If a pointer/cursor activation event occurs, the X,Y coordinate is compared to the previous event saved at both sites for that pointer. If the X,Y coordinates are different, the pointer-icon displayed is moved to the new location and a message is sent to the remote device which allows the remote device to do the same. The pointer-icon representing the programmer is then displayed on both systems telling both users that the

programmer was the last to move the pointer. This will display the effect of dragging a pointer icon at the remote location, when it is dragged at the local location. In one preferred embodiment, the programmer user's movement of a pointer icon takes precedence over that of the remote user and discards remote user commands if they are received while the programmer user is manipulating his local icons. This assures stable operation at the local site, allowing the physician at the programmer to maintain control to enable his rapid response to occurrences at the patient.

Referring now to Fig. 10a, the operation of either system to a remote command or screen change is outlined in flow chart 200. The incoming data is received 201, and separated into its component parts of relevance in step 202. For example, the ECG portion of data in block 95 (From Fig. 9) is forwarded without its header to step 203, and the process of updating the ECG or other physiologic signal waveform is accomplished. The pointer data from block 97 is sent to the process performed at step 204, and if no change is found 207, nothing further is done with that data. Likewise, the screen data areas are checked for changes (steps 205, 213 and updates of the relevant changes are made (step 213). If command information is received, it is transferred to processes at steps 209, 210 which determine if activation of these commands is appropriate, then the appropriate activation occurs, step 211, and then the display is again updated as needed 213.

In Fig 10b, the local control program steps that monitor and send out changes needed to be noticed by the remote system is outlined in flow chart 250. In the normal state, the operating system program is monitored such that the ECG buffer is maintained and locally updated 252. Any local commands initiated by pointer/cursor icon activation and movements of these pointers are kept track of 253, and any remote inputs related to any of these just mentioned data buffers may be received 258. A part of the inventive application program will then update all screen area indexes with the information from steps 252, 253, and 258, in step 254,

in accord with the detailed description above. A separate portion of this program will maintain and update the new pointer/cursor locations in step 255 so these can be painted over the display without affecting the underlying display screen buffer. For local only information regarding the screen display, the same manner of operation is maintained as for the pointer locations. A part of the monitoring program performs step 256 which checks to see whether there have been any changes locally that need to be sent to the remote system, or simply sends the relevant buffer information on the occurrence of a time-out, if preferred. The relevant data is then packaged and sent 257 and the system returns to the normal monitoring state.

While it will be apparent to the reader that many adaptations may be made of this disclosure, it is only limited by the following claims.

## \*\*\*\*\*APPENDIX\*\*\*\*\*

/\* These three code fragments have been excerpted from actual code files. They are presented here to illustrate a preferred embodiment  
5 Screen Capture processing procedure for finding changed areas of screens and allowing for compression of video RAM data which can then be sent to a remote location without loss of waveform fidelity\*/

/\* Main screen processing loop \*/

void

mnt\_ScreenTransfer::threadFn()

{

NG\_TRACE\_FUNCTION();

unsigned int index;

int minx, maxx, miny, maxy;

int new\_minx, new\_maxx, new\_maxy;

int x, y;

unsigned int checked;

bool doneCheckingScreenWorth;

unsigned int lastLeftOffIndex = 0;

prt\_ScreenInfo\* p\_screenInfo;

DATETIME dt;

mnt\_Ulong byte\_length;

/\*\*\*\*\*\* debug collection \*\*\*\*\*/

/\* open a file for debug collection \*/

if (v\_debugOn) {

```
p_v_ScreenFile = fopen("SCREEN.DAT", "w");
fclose(p_v_ScreenFile);          /* discard contents */
p_v_ScreenFile = fopen("SCREEN.DAT", "w");

5      }

    /****** end debug collection *****/

    try
    {
10      // printf("The ScrnThread is executing.\n");
      p_screenInfo = new prt_ScreenInfo;

      v_screenThreadIsActive = TRUE;
      //tbd add to main the call to declare time-to-become-inactive

15      while(v_screenThreadIsActive)
      {
          doneCheckingScreenWorth = FALSE;
          DosSleep(500L);

20          // Check to see if there is a change in environment
          // For example, maybe color was turned off
          checkEnvironment();

          screenCapture();
          screenCompare();

25          /****** debug collection *****/

          if (v_debugOn) {
```

// %4d means 4 places of decimal, %2x means 2 places of hex, % means  
an output

// Note to output that a screen capture/compare was done

fprintf(p\_v\_ScreenFile, "%.2d: %.2d: %.2d. %.2d screen  
capture/compare\n",

dt.hours, dt.minutes, dt.seconds, dt.hundredths);

fflush(p\_v\_ScreenFile);

// In order that debug file does not grow indefinitely, close after

// two minutes of collection.

DosGetDateTime(&dt); // Get Date & Time

if ( (dt.minutes - v\_dateTime.minutes) > 2) {

fflush(p\_v\_ScreenFile);

fclose(p\_v\_ScreenFile);

v\_debugOn = FALSE;

}

}

/\*\*\*\*\*DEBUG CODE COLLECT END \*\*\*\*\*/

// Find Rectangles and send

while (!doneCheckingScreenWorth)

{

index = lastLeftOffIndex;

y = index / v\_bytesPerRow;

x = index - (y \* v\_bytesPerRow);

minx = -1;

for (checked = 0; checked < v\_screenSizeInBytes; checked++)

```
{
    // Check flags until we have a rectangle to send.
    if (v_screenChangedFlagBuffer[index])
    {
5        // If we don't have a rectangle yet set one.
        if (minx == -1)
        {
            minx = maxx = x;
            miny = maxy = y;
10        }
        else
        {
            // Check the x and y gap spacing to see if we can include
            // this in the current rectangle.
15        if ((x >= minx - v_gapAllowedX) &&
            (x <= maxx + v_gapAllowedX) &&
            (y >= miny - v_gapAllowedY) &&
            (y <= maxy + v_gapAllowedY))
            {
20                // Determine the size of the new proposed rectangle.
                // We will not set this as the current rectangle
                // until we know that the area is not too large
                // for a single message.
                new_minx = minx;
                new_maxx = maxx;
25                new_maxy = maxy;
                if (x < new_minx)
                {
                    new_minx = x;
30                }
            }
        }
    }
}
```

```

else if (x > new_maxx)
{
    new_maxx = x;
}

// Since we are advancing in the y direction and we don't
// allow wrapped rectangles. We only need to adjust maxy.
if (y > new_maxy)
{
    new_maxy = y;
}

// Is the proposed block too big for a single message?
// Note that following doesn't work if right side set to less
than max
if (((new_maxy - miny + 1) * (new_maxx - new_minx +
1)) > v_maxSingleMessageSize)
{
    /****** debug collection *****/
    if (v_debugOn) {
        /* %4d means 4 places of decimal, %2x means 2
places of hex, % means an output */
        fprintf(p_v_ScreenFile, "        block-too-big test,
%6d <= index %5dx %5dy\n",
            index, x, y);
        fflush(p_v_ScreenFile);
    }
    /******DEBUG CODE COLLECT END
*****/

```



```

// Send the current block, and set an index
// to remember where we left off.
lastLeftOffIndex = index;
break;
5      }
else
{
    // Make the current block equal to the proposed block.
    minx = new_minx;
    maxx = new_maxx;
10     maxy = new_maxy;
}
}
else
15 {
    // If we went too far in the y direction,
    // send the current block, and look for the next
    // block where we left off.
    if (y > maxy + v_gapAllowedY)
20     {
        /****** debug collection *****/
        if (v_debugOn) {
            /* %4d means 4 places of decimal, %2x means 2 places of
hex, % means an output */
25             fprintf(p_v_ScreenFile, "          gap test\n");
            fflush(p_v_ScreenFile);
        }
        /******DEBUG CODE COLLECT END
******/
30

```

```

        lastLeftOffIndex = index;
        break;
    }
}
5      }
    }

    // Advance to the next coordinate.
    x++;
10    if (x >= v_bytesPerRow)
    {
        x = 0;
        y++;
        if (y >= v_maxScreenPixelsY)
15        {
            y = 0;
        }
    }

20    // Need to wrap back to the beginning?
    index++;
    if (index >= v_screenSizeInBytes)
    {
        /***** debug collection *****/
25        if (v_debugOn) {
            /* %4d means 4 places of decimal, %2x means 2 places of hex,
% means an output */
            fprintf(p_v_ScreenFile, "        doneScreenWorth/wrap
test\n");
30            fflush(p_v_ScreenFile);

```

}

/\*\*\*\*\*DEBUG CODE COLLECT END

\*\*\*\*\*/

5 // Added

doneCheckingScreenWorth = TRUE;

index = 0;

// If we found some changes, send that area. Otherwise,

10 // setting index=0 leads to looking for more changes

//at the top of the screen.

if (minx != -1)

{

lastLeftOffIndex = index;

15 break;

}

}

} // end "for" checking all up to v\_screenSizeInBytes

20

/\*\*\*\*\* "break" statements on "for" above end up here

\*\*\*\*\*/

// Did we find a rectangle?...indicated by minx not being -1

if (minx != -1)

25 {

byte\_length = getScreenRect(minx \* v\_pixelsPerByte,

miny,

(maxx + 1)\*v\_pixelsPerByte-1,

maxy);

30

```

p_screenInfo->header.x1 = minx * v_pixelsPerByte;
p_screenInfo->header.y1 = miny;
p_screenInfo->header.x2 = (maxx + 1)*v_pixelsPerByte-1;
p_screenInfo->header.y2 = maxy;
5      p_screenInfo->header.skip = 0;// number of horizontal lines that
are skipped between each line

p_screenInfo->header.format = v_colorFormat;
p_screenInfo->header.compression = prc_comp_rlCompression;
// Set pointer to rectangle data.
10      p_screenInfo->p_data = v_sendRectangleBuffer;

/***** debug collection *****/
if (v_debugOn) {
    /* %4d means 4 places of decimal, %2x means 2 places of hex, %
15      means an output */
    DosGetDateTime(&dt);          // Get Date & Time
    fprintf(p_v_ScreenFile, "%.2d: %.2d: %.2d. %.2d ",
        dt.hours, dt.minutes, dt.seconds, dt.hundredths);
    fprintf(p_v_ScreenFile, "sending
20      Index => %7dlength=> %5d%6d%6d%6d%6d\n",
        lastLeftOffIndex, byte_length, minx, maxx, miny, maxy);
    fflush(p_v_ScreenFile);
}
/*****DEBUG CODE COLLECT END *****/

25      // Send the current screen rectangle.
// For now ignoring the return from sendScreenData call
v_p_screenDataMsg->sendScreenData(p_screenInfo,
v_pixelsPerByte);
30

```

```
        } // end if we found a rectangle (i.e. minx != -1)
    } // end while notDoneCheckingScreen's Worth
} // end while screenThreadActive
```

```
5      delete p_screenInfo;
```

```
        // printf("The ScrnThread is exiting.\n");
```

```
    }
```

```
10   catch (...)
```

```
    {
```

```
        // No Return
```

```
        SYD_systemError(IString("mnt_Screen in catch...some uncaught
exception"));
```

```
15     }
```

```
    }
```

```
/* Function to read video memory */
```

```
20   void
```

```
mnt_ScreenTransfer::screenCapture()
```

```
    {
```

```
        NG_TRACE_FUNC();
```

```
25         unsigned char      *p_dive = NULL;
```

```
        unsigned char      *p_current = NULL;
```

```
        unsigned int       line = 0;
```

```
        unsigned int       i = 0;
```

```
        unsigned char      mono_pixels = 0;
```

```
30
```

```
// remove the pointer from the screen.
```

```
WinShowPointer(HWND_DESKTOP, false);
```

```
5      p_dive= (unsigned char *)v_p_diveFrameBuffer;
```

```
p_current= v_currentScreenBuffer;
```

```
      if ((v_pixelsPerByte == 8) && (v_platform ==  
10     syt_Programmer::c_486Color9790)) {
```

```
          // BW on Color 9790 Screen capture
```

```
          for(line = 0; line < v_maxScreenPixelsY; line++)
```

```
          {
```

```
              for(i = 0; i < v_maxScreenPixelsX; i++)
```

```
              {
```

```
                  mono_pixels < <= 1;
```

```
                  if (*p_dive++)
```

```
                  {
```

```
                      mono_pixels |= 1;
```

```
                  }
```

```
                  if ((i % 8) == 7)
```

```
                  {
```

```
                      *p_current++ = mono_pixels;
```

```
                  }
```

```
              }
```

```
              p_dive+= mnc_486CUnusedDiveSection;;
```

```
          }
```

```
      } // end on if 486C and color off
```

```
else if (v_pixelsPerByte == 8) {  
  
    // 386/486EL platform 9790 Screen capture  
    for(line = 0; line < v_maxScreenPixelsY; line++)  
    {  
5        for(i = 0; i < v_bytesPerRow; i++)  
        {  
            *p_current++ = *p_dive++;  
        }  
10    }  
    } //end if 386/486EL  
  
else if (v_pixelsPerByte == 1)  
{  
15  
    // Color Screen capture  
    /* Copy data from the frame buffer to the memory bitmap. */  
    for(line = 0; line < v_maxScreenPixelsY; line++)  
    {  
20        for(i = 0; i < v_maxScreenPixelsX; i++)  
        {  
            *p_current++ = *p_dive++;  
        } // end "for" to copy x  
  
25        p_dive+ = mnc_486CUnusedDiveSection;;  
        } // end "for" to copy y  
  
    } // end if 486C and color on  
  
30    else {
```

```
SYD_systemError(IString("in screen compare and v_pixelsPerByte not 8  
nor 1") +
```

```
    IString(v_pixelsPerByte));
```

```
}
```

```
// display the pointer on the screen.
```

```
WinShowPointer(HWND_DESKTOP, true);
```

```
}
```

```
/* Function to find changed rectangles */
```

```
void
```

```
mnt_ScreenTransfer::screenCompare()
```

```
{
```

```
    NG_TRACE_FUNC();
```

```
    unsigned int index;
```

```
    unsigned char current;
```

```
    // printf("The screenCompare is executing.\n");
```

```
    index = 0;
```

```
    while (index < v_screenSizeInBytes)
```

```
    {
```

```
        // compare algorithm is to compare and if different,
```

```
        // copy "current" into "previous" and set a
```

```
        // flag in screenChangedFlagBuffer
```

```
        current = v_currentScreenBuffer[index];
```

```
        if (current != v_previousScreenBuffer[index])
```



```
        {  
            v_previousScreenBuffer[index] = current;  
            v_screenChangedFlagB  
uffer[index] = 0xFF;  
5         }  
        index++;  
  
    } // end while index < screenSizeInBytes.  
  
10    // printf("The screenCompare is exiting.\n");  
    }
```

What is claimed is:

1. A programmer device for use in a medical communications system for communicating in near real time information from between at least two remote sites, one remote site at a patient location having a programmer device which has a programmer generated display, and an other (of said at least two remote sites) at an expert location having a computing device with a computing device generated display, each location having available substantially similar screen displays, such that information related to an implantable medical device and a patient at said patient location remote site can be reviewed simultaneously on said substantially similar displays at said at least two remote sites facilitated by data communications transferred across a communication line between said at least two remote sites, said programmer device being configurable to perform various operations by executing programs through a microprocessor and memory system and comprising:

a physiologic signal device connection, connected to said programmer device for receiving electrical output representing a patient's physiologic signal waveform, and for producing a signal suitable for use by a programmer screen display operating program for generating a display from said electrical output at at least one display area including at least a physiologic waveform signal display area and producing instantaneous changes in said at least one display area, at least one of said changes representative of changes in said waveform display,

said programmer display operating program, employing at least;

a first video display data buffer for holding a video data representation of information displayed in one of said at least one display areas of said programmer generated display,

a second video display buffer for holding data representing instantaneous changes in at least one of said areas,

a display generating program for using a data image of said video data representation in said first video display buffer for producing said programmer generated display,

5           an index generating program for reviewing data in said first video display buffer and creating a first index buffer corresponding to said at least one of said display areas, said index generating program indicating in said first index buffer by storing data therein representing which of all locations in said at least one area have changed from a previous review, and for capturing a data representation of said  
10       changed locations in a capture buffer and,

a sending program for packaging data comprising contents of said first index buffer and said capture buffer in appropriately encoded format, and for sending said appropriately formatted index buffer data across said communication line.

15           2. A programmer device as set forth in claim 1, said display generating program further comprising a two color display generating program for interpreting said physiologic signal waveform as two color display data, and wherein said index  
20       generating program has a data compression program for receiving said physiologic waveform index data and coding it such that for each byte, one bit is set to indicate whether a change has occurred in that byte and such that for the entire physiologic waveform index buffer, a compressed physiologic waveform index is prepared.

25           3. A system as set forth in claim 1 wherein said programmer operating program further comprises;

30           a pointer/cursor coordination program having a buffer for holding at least location information for each pointer/cursor to be coordinated, and having a

monitoring means for updating any programmer generated display change in pointer/cursor activation and location, said monitoring means updating each said pointer/cursor buffer with any change in location information from a last review, said location information being changeable responsive to pointer/cursor user controls based on a local user changing location status of any pointer/cursor under local control, and wherein said pointer/cursor coordinating program further comprises a buffer for containing information regarding at least location status of each remote pointer that is to be displayed on said patient location display, and

wherein said patient location screen display operating program further comprises;  
a program for receiving new information for each said remote pointer/cursor buffer and operating on such data to produce a display of said remote pointer/cursor in accord with the data in said remote pointer/cursor buffer such that any changes in the location data of a remote pointer/cursor buffer results in a change in location on the display of that remote pointer/cursor on the patient location display screen.

4. A programmer as set forth in claim 3 wherein said pointer cursor operating program further comprises an activation buffer for maintaining activation status for each pointer/cursor capable of activation.

5. A programmer device as set forth in claim 2, wherein said sending program further comprises a pointer data capture program for capturing and then for sending the data in said pointer/cursor buffer to said communication line.

6. A system as set forth in claim 3 further comprising;

a program for monitoring which of all said pointer/cursors is active such that said active cursor/pointer may initiate a command, and for maintaining a data buffer containing such monitored information.

7. A computing device operating program for coordinating a physiologic waveform display with a programmer generated display as set forth in claims 1 - 6,  
5 comprising

communication means to receive data sent by said programmer device and to produce a physiologic waveform display therefrom.

10 8 A computing device operating program for displaying an image substantially the same as the display on the programmer generated display having communications means to receive data sent by said programmer device set forth in claims 1-6 and generating a substantially similar display therefrom.

15 9. A system for displaying substantially the same image on at least two remote locations having a programmer device and a computing device as set forth in claim

10Method for communicating between at least two remote locations so as to enable coordinated display of a physiologic waveform and pointer/cursor information  
20 comprising;

capturing pointer/cursor information regarding a location on a display screen for each said pointer/cursor,

25 redacting image data from a video display buffer based on said pointer/cursor information so that the remaining video buffer data represents a display sans said pointer/cursors

reviewing the redacted video image buffer so as to locate any changes since a last review,

creating an index of information describing which locations in said video buffer contain changed data since said last review,

capturing representations of the images at the changed locations and storing this as data in a buffer,

compressing the index and the capture buffer data,

5 sending the compressed index and capture buffer data from one of said at least two locations.

11. A method as set forth in claim 10 wherein said pointer/cursor data is sent in said sending step.

10 12. A method of communicating between at least two remote locations so as to enable coordinated display of a physiologic waveform and pointer/cursor information comprising:

receiving compressed index and capture data across a communication line from one of said at least two locations at a first of said at least two locations,


15 decompressing said index and capture buffer data,

swapping in information from said capture buffer data at locations in a video display buffer representing corresponding locations to those indicated in said index data so as to enable a display at said first location to display said changes.




20 13. A method as set forth in claim 12 further comprising the step of receiving data representing pointer/cursor location on a display screen from said one location of at least two remote sites and still further comprising the step of displaying an iconic image of a pointer/cursor representing a pointer displayed at said one remote location in a location on the screen in said first locations indicated by the received  
25 representative pointer /cursor location data.

1/11



Programmer




Remote "Experts"




2/11











5/11



6/11






Fig. 106

LOCAL CONTROL PROGRAM

7/11



8/11



9/11




Fig. 12

10/11

Session Call Remote Reports Windows Setup

CP

FREEZE

ECG

Minix 8340

PACING PARAMETERS

Rate 70 ppm

Hysteresis OFF bpm

Refractory 325 ms

Amplitude 5.0 V

Pulse Width 1.5 ms

Sensitivity 2.5 mV

Polarity Bipolar

Status Reset

PENDING 123

Rate

Rate	Present	Nominal
44	50	79
45	59	80
46	60	81
47	61	82
48	62	83
49	63	84
50	64	85

MAC SCREEN

"Button Press"

Selected

Indicates

Button Press is

Active.

122

130

132

131

134

133

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

290

291

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320

321

322

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

346

347

348

349

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

380

381

382

383

384

385

386

387

388

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

478

479

480

481

482

483

484

485

486

487

488

489

490

491

492

493

494

495

496

497

498

499

500

501

502

503

504

505

506

507

508

509

510

511

512

513

514

515

516

517

518

519

520

521

522

523

524

525

526

527

528

529

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

546

547

548

549

550

551

552

553

554

555

556

557

558

559

560

561

562

563

564

565

566

567

568

569

570

571

572

573

574

575

576

577

578

579

580

581

582

583

584

585

586

587

588

589

590

591

592

593

594

595

596

597

598

599

600

601

602

603

604

605

606

607

608

609

610

611

612

613

614

615

616

617

618

619

620

621

622

623

624

625

626

627

628

629

630

631

632

633

634

635

636

637

638

639

640

641

642

643

644

645

646

647

648

649

650

651

652

653

654

655

656

657

658

659

660

661

662

663

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

697

698

699

700

701

702

703

704

705

706

707

708

709

710

711

712

713

714

715

716

717

718

719

720

721

722

723

724

725

726

727

728

729

730

731

732

733

734

735

736

737

738

739

740

741

742

743

744

745

746

747

748

749

750

751

752

753

754

755

756

757

758

759

760

761

762

763

764

765

766

767

768

769



11/11

143

Session Call Remote Reports Windows Setup

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

290

291

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320

321

322

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

346

347

348

349

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

380

381

382

383

384

385

386

387

388

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

478

479

480

481

482

483

484

485

486

487

488

489

490

491

492

493

494

495

496

497

498

499

500

501

502

503

504

505

506

507

508

509

510

511

512

513

514

515

516

517

518

519

520

521

522

523

524

525

526

527

528

529

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

546

547

548

549

550

551

552

553

554

555

556

557

558

559

560

561

562

563

564

565

566

567

568

569

570

571

572

573

574

575

576

577

578

579

580

581

582

583

584

585

586

587

588

589

590

591

592

593

594

595

596

597

598

599

600

601

602

603

604

605

606

607

608

609

610

611

612

613

614

615

616

617

618

619

620

621

622

623

624

625

626

627

628

629

630

631

632

633

634

635

636

637

638

639

640

641

642

643

644

645

646

647

648

649

650

651

652

653

654

655

656

657

658

659

660

661

662

663

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

697

698

699

700

701

702

703

704

705

706

707

708

709

710

711

712

713

714

715

716

717

718

719

720

721

722

723

724

725

726

727

728

729

730

731

732

733

734

735

736

737

738

739

740

741

742

743

744

745

746

747

748

749

750

751

752

753

754

755

756

757

758

759

760

761

762

763

764

765

766

767

768

769

770

771

772

773

774

775

776

777

778

779

780

781

782

783

784

785

786

787

788

789

790

791

792

793

794

795

796

797

798

799

800

801

802

803

804

805

806

807

808

809

810

811

812

813

814

815

816

817

818

819

820

821

822

823

824

825

826

827

828

829

830

831

832

833

834

835

836

837

838

839

840

841

842

843

844

845

846

847

848

849

850

851

852

853

854

855

856

857

858

859

860

861

862

863

864

865

866

867

868

869

870

871

872

873

874

875

876

877

878

879

880

881

882

883

884

885

886

887

888

889

890

891

892

893

894

895

896

897

898

899

900

901

902

903

904

905

906

907

908

909

910

911

912

913

914

915

916

917

918

919

920

921

922

923

924

925

926

927

928

929

930

931

932

933

934

935

936

937

938

939

940

941

942

943

944

945

946

947

948

949

950

951

952

953

954

955

956

957

958

959

960

961

962

963

964

965

966

967

968

969

970

971

972

973

974

975

976

977

978

979

980

981

982

983

984

985

986

987

988

989

990

991

992

993

994

995

996

997

998

999

1000

1001

1002

1003

1004

1005

1006

1007

1008

1009

1010

1011

1012

1013

1014

1015

1016

1017

1018

1019

1020

1021

1022

1023

1024

1025

1026

1027

1028

1029

1030

1031

1032

1033

1034

1035

1036

1037

1038

1039

1040

1041

1042

1043

1044

1045

1046

1047

1048

1049

1050

1051

1052

1053

1054

1055

1056

1057

1058

1059

1060

1061

1062

1063

1064

1065

1066

1067

1068

1069

1070

1071

1072

1073

1074

1075

1076

1077

1078

1079

1080

1081

1082

1083

1084

1085

1086

1087

1088

1089

1090

1091

1092

1093

1094

1095

1096

1097

1098

1099

1100

1101

1102

1103

1104

1105

1106

1107

1108

1109

1110

1111

1112

1113

1114

1115

1116

1117

1118

1119

1120

1121

1122

1123

1124

1125

1126

1127

1128

1129

1130

1131

1132

1133

1134

1135

1136

1137

1138

1139

1140

1141

1142

1143

1144

1145

1146

1147

1148

1149

1150

1151

1152

1153

1154

1155

1156

1157

1158

1159

1160

1161

1162

1163

1164

1165

1166

1167

1168

1169

1170

1171

1172

1173

1174

1175

1176

1177

1178

1179

1180

1181

1182

1183

1184

1185

1186

1187

1188

1189

1190

1191

1192

1193

1194

1195

1196

1197

1198

1199

1200

1201

1202

1203

1204

1205

1206

1207

1208

1209

1210

1211

1212

1213

1214

1215

1216

1217

1218

1219

1220

1221

1222

1223

1224

1225

1226

1227

1228

1229

1230

1231

1232

1233

1234

1235

1236

1237

1238

1239

1240

1241

1242

1243

1244

1245

1246

1247

1248

1249

1250

1251

1252

1253

1254

1255

1256

1257

1258

1259

1260

1261

1262

1263

1264

1265

1266

1267

1268

1269

1270

1271

1272

1273

1274

1275

1276

1277

1278

1279

1280

1281

1282

1283

1284

1285

1286

1287

1288

1289

1290

1291

1292

1293

1294

1295

1296

1297

1298

1299

1300

1301

1302

1303

1304

1305

1306

1307

1308

1309

1310

1311

1312

1313

1314

1315

1316

1317

1318

1319

1320

1321

1322

1323

1324

1325

1326

1327

1328

1329

1330

1331

1332

1333

1334

1335

1336

1337

1338

1339

1340

1341

1342

1343

1344

1345

1346

1347

1348

1349

1350

1351

1352

1353

1354

1355

1356

1357

1358

1359

1360

1361

1362

1363

1364

1365

1366

1367

1368

1369

1370

1371

1372

1373

1374

1375

1376

1377

1378

1379

1380

1381

1382

1383

1384

1385

1386

1387

1388

1389

1390

1391

1392

1393

1394

1395

1396

1397

1398

1399

1400

1401

1402

1403

1404

1405

1406

1407

1408

1409

1410

1411

1412

1413

1414

1415

1416

1417

1418

1419

1420

1421

1422

1423

1424

1425

1426

1427

1428

1429

1430

1431

1432

1433

1434

1435

1436

1437

1438

1439

1440

1441

1442

1443

1444

1445

1446

1447

1448

1449

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US98/06085

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : A61N 1/37

US CL : 128/903, 905; 607/ 26, 27, 32

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 128/903,905; 607/26,27,32

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

APS

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y, E	US 5,752,977 A (GREVIOUS et al.) 19 May 1998, cols. 1-5, col. 7 lines 16-42, and col. 11 line 47 to col. 19.	1-13
Y	US 5,487,755 A (SNELL et al.) 30 January 1996, Abstract, cols. 1-8, col. 14 lines 14-46, and cols. 17-25.	1-13
Y	US 5,487,754 A (SNELL et al.) 30 January 1996, entire document.	1-13
Y	US 5,431,691 A (SNELL et al.) 11 July 1995, entire document.	1-13
Y	US 5,309,919 A (SNELL et al.) 10 May 1994, entire document.	1-13



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A* document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*E* earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*g* document member of the same patent family
*O* document referring to an oral disclosure, use, exhibition or other means	
*P* document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

16 JUNE 1998

Date of mailing of the international search report

20 JUL 1998

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

STEPHEN HUANG

Telephone No. (703) 308-3399

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**